



Speed Control Sensor ALS100/D ATEX

Art No: 3060007

Multi voltage construction for
direct connection to:
18 - 50VDC
18 - 240VAC /50/60Hz
signal relay contact







 II 3G Ex nAc IIC T6 Gc X

Compact speed- and dwell indicator with two switchable speed ranges. Can be applied as single speed monitor with upper and lower limit or as dwell indicator. Multi voltage input means that without switching the sensor can be operated via direct voltage or alternating voltage. Inductive measuring principle (corresponds to metal) for stable and precise results.

Technical data:

Connection voltage	18-50VDC/18-240VAC	protection class IP65
Speed ranges	low: 6-150 U/Min	high: 120-3000 U/Min adjustable
Switching delay	fix 9-15s, acc. to speed	
Current consumption	max 20mA	
Switching delay	depending on speed	(1 impulse/sec. output self adjustable)
Signal output	pot-free relais contact	max: 1A 240VAC (cos phi 1)
Signal light	LED integrated	
Temperature range	-20 up to + 70° C	integrated thermo fuse 70°C
Housing	nickel-plated brass	sizes M30x1.5 x L= 78mm
Connection cable	length 2m (5 x 0.35mm ²), grey, with single wire colours	See operating manual.
Application according to ATEX in Zone 22		



Technical changes in the sense of technological progress reserved at all times!
email: info@agromatic.com
www.agromatic.com

Switzerland (head office)
Agromatic AG
CH-8637 Laupen
Tel. (+41) 55 256 21 00
Fax (+41) 55 256 21 11

Germany
Agromatic GmbH
D - 01454 Radeberg
Tel. (+49) 3528 4521 45
Fax (+49) 3528 4875 32